

Contents

| | |
|---|---------------|
| Preface | xv |
| List of Symbols | xxv |
| List of Examples | xxxiii |
| Acknowledgment | xxxv |
| 1 Introduction | 1 |
| 1.1 Basic Concepts | 1 |
| 1.2 Design Process | 5 |
| 1.3 Composites Design Methods | 8 |
| 1.4 Fracture Mechanics | 10 |
| 1.5 Design for Reliability | 12 |
| 1.5.1 Stochastic Representation | 13 |
| 1.5.2 Reliability-Based Design | 16 |
| 1.5.3 Load and Resistance Factor Design | 18 |
| 1.5.4 Determination of Resistance Factors | 20 |
| 1.5.5 Determination of Load Factors | 21 |
| 1.5.6 Basis Values | 22 |
| 1.5.7 Limit States Design | 27 |
| Problems | 27 |
| 2 Materials | 37 |
| 2.1 Fiber Reinforcements | 38 |
| 2.2 Fiber Types | 39 |
| 2.2.1 Glass Fibers | 39 |
| 2.2.2 Silica and Quartz Fibers | 40 |
| 2.2.3 Carbon Fibers | 41 |
| 2.2.4 Carbon Nanotubes | 43 |
| 2.2.5 Organic Fibers | 45 |
| 2.2.6 Boron Fibers | 46 |
| 2.2.7 Ceramic Fibers | 46 |
| 2.2.8 Basalt Fibers | 46 |
| 2.2.9 Metallic Fibers | 47 |

| | | |
|----------|---|------------|
| 2.2.10 | Natural Fibers | 47 |
| 2.3 | Fiber-Matrix Compatibility | 48 |
| 2.4 | Fiber Forms | 49 |
| 2.4.1 | Continuous and Discontinuous Fibers | 49 |
| 2.4.2 | 1D Textiles: Strand, Tow, End, Yarn, and Roving | 51 |
| 2.4.3 | 2D Textiles: Fabrics | 53 |
| 2.5 | Matrix Materials | 56 |
| 2.6 | Thermoset Matrices | 59 |
| 2.6.1 | Polyester Resins | 60 |
| 2.6.2 | Vinyl Ester Resins | 62 |
| 2.6.3 | Epoxy Resins | 62 |
| 2.6.4 | Phenolic Resins | 63 |
| 2.7 | Thermoplastic Matrices | 64 |
| 2.8 | Biodegradable Matrices | 64 |
| 2.9 | Creep, Temperature, and Moisture | 65 |
| 2.10 | Corrosion Resistance | 69 |
| 2.11 | Flammability | 70 |
| | Problems | 71 |
| 3 | Manufacturing Processes | 85 |
| 3.1 | Hand Layup | 86 |
| 3.2 | Prepreg Layup | 88 |
| 3.3 | Bag Molding | 89 |
| 3.4 | Autoclave Processing | 90 |
| 3.5 | Compression Molding | 92 |
| 3.6 | Resin Transfer Molding | 93 |
| 3.7 | Vacuum-Assisted Resin Transfer Molding | 95 |
| 3.8 | Pultrusion | 97 |
| 3.9 | Filament Winding | 99 |
| 3.10 | Textile Manufacturing | 102 |
| 3.10.1 | Woven Fabrics | 102 |
| 3.10.2 | Knitted Fabrics | 103 |
| 3.10.3 | Braid Fabrics | 104 |
| 3.10.4 | Stitched Fabrics | 104 |
| | Problems | 105 |
| 4 | Micromechanics | 107 |
| 4.1 | Basic Concepts | 108 |
| 4.1.1 | Volume and Mass Fractions | 108 |
| 4.1.2 | Representative Volume Element | 110 |
| 4.1.3 | Heterogeneous Material | 112 |
| 4.1.4 | Anisotropic Material | 112 |
| 4.1.5 | Orthotropic Material | 113 |
| 4.1.6 | Transversely Isotropic Material | 113 |
| 4.1.7 | Isotropic Material | 113 |

| | | |
|----------|--|------------|
| 4.2 | Stiffness | 113 |
| 4.2.1 | Longitudinal Modulus | 114 |
| 4.2.2 | Transverse Modulus | 116 |
| 4.2.3 | In-Plane Poisson’s Ratio | 117 |
| 4.2.4 | In-Plane Shear Modulus | 118 |
| 4.2.5 | Intralaminar Shear Modulus | 121 |
| 4.2.6 | Restrictions on the Elastic Constants | 122 |
| 4.3 | Moisture and Thermal Expansion | 123 |
| 4.3.1 | Thermal Expansion | 123 |
| 4.3.2 | Moisture Expansion | 125 |
| 4.3.3 | Transport Properties | 126 |
| 4.4 | Temperature-Dependent Properties | 127 |
| 4.4.1 | Micromechanics of CTE | 127 |
| 4.4.2 | Temperature Dependence | 128 |
| 4.5 | Strength | 131 |
| 4.5.1 | Longitudinal Tensile Strength | 132 |
| 4.5.2 | Longitudinal Compressive Strength | 135 |
| 4.5.3 | Transverse Tensile Strength | 136 |
| 4.5.4 | Mode I Fracture Toughness | 137 |
| 4.5.5 | In-Plane Shear Strength | 139 |
| 4.5.6 | Mode II Fracture Toughness | 141 |
| 4.5.7 | Transverse Compressive Strength | 142 |
| 4.5.8 | Mohr–Coulomb Failure | 142 |
| 4.5.9 | Intralaminar Shear Strength | 146 |
| | Problems | 147 |
| 5 | Ply Mechanics | 151 |
| 5.1 | Coordinate Systems | 151 |
| 5.2 | Stress and Strain | 151 |
| 5.2.1 | Stress | 152 |
| 5.2.2 | Strain | 155 |
| 5.3 | Stress–Strain Equations | 156 |
| 5.4 | Off-Axis Stiffness | 161 |
| 5.4.1 | Coordinate Transformations | 161 |
| 5.4.2 | Stress and Strain Transformations | 162 |
| 5.4.3 | Stiffness and Compliance Transformations | 166 |
| 5.4.4 | Specially Orthotropic Lamina | 169 |
| | Problems | 170 |
| 6 | Macromechanics | 173 |
| 6.1 | Plate Stiffness and Compliance | 174 |
| 6.1.1 | Assumptions | 174 |
| 6.1.2 | Strains | 176 |
| 6.1.3 | Stress Resultants | 179 |
| 6.1.4 | Plate Stiffness and Compliance | 180 |

| | | |
|----------|---|------------|
| 6.2 | Computation of Stresses | 185 |
| 6.3 | Common Laminate Types | 187 |
| 6.3.1 | Laminate Description | 187 |
| 6.3.2 | Symmetric Laminates | 188 |
| 6.3.3 | Antisymmetric Laminate | 189 |
| 6.3.4 | Balanced Laminate | 189 |
| 6.3.5 | Quasi-isotropic Laminates | 190 |
| 6.3.6 | Cross-Ply Laminate | 193 |
| 6.3.7 | Angle-Ply Laminate | 194 |
| 6.3.8 | Specially Orthotropic Laminate | 194 |
| 6.4 | Laminate Moduli | 196 |
| 6.4.1 | Trace-Normalized Moduli | 197 |
| 6.5 | Universal Carpet Plots | 199 |
| 6.5.1 | Homogenization | 204 |
| 6.5.2 | Membrane-Controlled design | 205 |
| 6.5.3 | Bending-Controlled design | 210 |
| 6.6 | Hygrothermal Stress | 213 |
| | Problems | 221 |
| 7 | Strength | 227 |
| 7.1 | Lamina Failure Criteria | 230 |
| 7.1.1 | Strength Ratio | 230 |
| 7.1.2 | Maximum Stress Criterion | 231 |
| 7.1.3 | Maximum Strain Criterion | 233 |
| 7.1.4 | Interacting Failure Criterion | 236 |
| 7.1.5 | Hygrothermal Failure | 242 |
| 7.2 | First Ply Failure | 243 |
| 7.2.1 | In Situ Strength | 246 |
| 7.3 | Last Ply Failure | 252 |
| 7.3.1 | Ply Discount | 252 |
| 7.3.2 | Truncated-Maximum-Strain Criterion | 255 |
| 7.4 | Laminate Strength | 261 |
| 7.4.1 | Universal Carpet Plots: In-Plane Strength | 262 |
| 7.5 | Stress Concentrations | 271 |
| 7.5.1 | Notched Plate under In-Plane Load | 273 |
| | Problems | 278 |
| 8 | Damage | 283 |
| 8.1 | Continuum Damage Mechanics | 283 |
| 8.2 | Longitudinal Tensile Damage | 285 |
| 8.3 | Longitudinal Compressive Damage | 288 |
| 8.4 | Transverse Tension and In-Plane Shear | 292 |
| 8.4.1 | Limitations | 295 |
| 8.4.2 | Approximations | 295 |
| 8.4.3 | Displacement Field | 296 |

| | | |
|-----------|---|------------|
| 8.4.4 | Strain Field | 297 |
| 8.4.5 | Laminate Reduced Stiffness | 297 |
| 8.4.6 | Lamina Reduced Stiffness | 297 |
| 8.4.7 | Fracture Energy | 298 |
| 8.4.8 | Solution Algorithm | 299 |
| 8.4.9 | Lamina Iterations | 300 |
| 8.4.10 | Laminate Iterations | 300 |
| | Problems | 301 |
| 9 | Fabric-reinforced Composites | 303 |
| 9.1 | Weave Pattern Description | 303 |
| 9.2 | Analysis | 307 |
| 9.3 | Tow Properties | 310 |
| 9.4 | Element Stiffness and Constitutive Relationship | 315 |
| 9.4.1 | Bending-Restrained Model | 315 |
| 9.4.2 | Bending-Allowed Model | 317 |
| 9.5 | Laminate Properties | 318 |
| 9.5.1 | Elastic Constants | 318 |
| 9.5.2 | Thermal and Moisture Expansion Coefficients | 319 |
| 9.6 | Failure Analysis | 321 |
| 9.6.1 | Stress Analysis | 321 |
| 9.6.2 | Damage Initiation, Evolution, and Fracture | 323 |
| 9.6.3 | Cross-Ply Approximation | 327 |
| 9.7 | Woven Fabrics with Gap | 331 |
| 9.8 | Twill and Satin | 333 |
| 9.8.1 | Twill Weave with $n_g > 2, n_s = 1, n_i = 1$ | 334 |
| 9.8.2 | Twill Weave with $n_s = 1$ | 337 |
| 9.8.3 | Satin Weave with $n_i = 1$ | 338 |
| 9.8.4 | Twill and Satin Thermo-Elastic Properties | 340 |
| 9.9 | Randomly Oriented Reinforcement | 341 |
| 9.9.1 | Elastic Moduli | 342 |
| 9.9.2 | Strength | 343 |
| | Problems | 344 |
| 10 | Beams | 351 |
| 10.1 | Preliminary Design | 353 |
| 10.1.1 | Design for Deflections | 356 |
| 10.1.2 | Design for Strength | 357 |
| 10.1.3 | Design for Buckling | 359 |
| 10.1.4 | Column Behavior | 360 |
| 10.2 | Thin-Walled Beams | 362 |
| 10.2.1 | Wall Constitutive Equations | 366 |
| 10.2.2 | Neutral Axis of Bending and Torsion | 368 |
| 10.2.3 | Axial Stiffness | 370 |
| 10.2.4 | Mechanical Center of Gravity | 371 |

| | | |
|-----------|--|------------|
| 10.2.5 | Bending Stiffness | 372 |
| 10.2.6 | Torsional Stiffness | 378 |
| 10.2.7 | Shear of Open Sections | 380 |
| 10.2.8 | Shear of Single-Cell Closed Section | 389 |
| 10.2.9 | Beam Deformations | 391 |
| 10.2.10 | Segment Deformations and Stresses | 392 |
| 10.2.11 | Restrained Warping of Open Sections | 395 |
| | Problems | 396 |
| 11 | Plates and Stiffened Panels | 399 |
| 11.1 | Plate Bending | 400 |
| 11.1.1 | Universal Carpet Plots: Flexural Strength | 400 |
| 11.2 | Plate Buckling | 403 |
| 11.2.1 | All Edges Simply Supported | 404 |
| 11.2.2 | All Sides Clamped | 406 |
| 11.2.3 | One Free Edge | 406 |
| 11.2.4 | Biaxial Loading | 407 |
| 11.2.5 | Fixed Unloaded Edges | 407 |
| 11.3 | Stiffened Panels | 408 |
| 11.3.1 | Stiffened Panels under Bending Loads | 409 |
| 11.3.2 | Stiffened Panel under In-Plane Loads | 414 |
| | Problems | 420 |
| 12 | Shells | 423 |
| 12.1 | Shells of Revolution | 425 |
| 12.1.1 | Symmetric Loading | 426 |
| 12.2 | Cylindrical Shells with General Loading | 434 |
| | Problems | 440 |
| 13 | Strengthening of Reinforced Concrete | 443 |
| 13.1 | Strengthening Design | 445 |
| 13.2 | Materials | 447 |
| 13.2.1 | Concrete | 448 |
| 13.2.2 | Steel Reinforcement | 449 |
| 13.2.3 | FRP | 449 |
| 13.3 | Flexural Strengthening of RC Beams | 449 |
| 13.3.1 | Unstrengthened Behavior | 450 |
| 13.3.2 | Strengthened Behavior | 450 |
| 13.3.3 | Analysis | 451 |
| 13.3.4 | Strong Strengthening Configuration (SSC) | 453 |
| 13.3.5 | Weak Strengthening Configuration (WSC) | 455 |
| 13.3.6 | Balanced Strengthening Configuration (BSC) | 457 |
| 13.3.7 | Serviceability Limit States | 458 |
| 13.3.8 | Summary Design Procedure: Bending | 464 |
| 13.4 | Shear Strengthening | 469 |

| | | |
|---------------------|---|------------|
| 13.4.1 | Summary Design Procedure: Shear | 473 |
| 13.5 | Beam-Column | 476 |
| 13.5.1 | Column: Pure Axial Compression | 477 |
| 13.5.2 | Summary Design Procedure: Column | 480 |
| 13.5.3 | Beam-Column: Combined Axial Compression and Bending | 483 |
| 13.5.4 | Summary Verification Procedure: Beam-Column | 489 |
| | Exercises | 498 |
| Appendix A | | 501 |
| A.1 | SCILAB Code for Classical Lamination Theory | 501 |
| A.2 | Periodic Microstructure Micromechanics | 501 |
| A.3 | Longitudinal Compressive Strength | 504 |
| Bibliography | | 511 |
| Index | | 525 |